



# LIFTING


## LANAC G100

Koristi se u priveznicama sa lancem za potrebe podizanja.

Legirani čelik. Približno 25% jači od legiranog lanca G80.

Završna obrada: ofarbano ili plastificirano prahom.

Testirano na proveru opterećenja pri 2,5 puta većoj vrednosti od dozvoljenog radnog opterećenja.



Šifra	Dim. lanca (mm)	Korak (mm)	Vanjska širina (mm)	Nosivost		Min. prekidna sila	Težina	Product Code
	A	B	C	t	kN	kN	kg/m	
G10S0618	6	18	22.2	1.4	35.3	56.5	0.8	
G10S0824	8	24	29.6	2.5	62.8	101	1.4	
G10S1030	10	30	37	4	98.1	157	2.2	
G10S1339	13	39	48.1	6.7	166	265	3.8	
G10S1648	16	48	59.2	10	251	402	5.7	
G10S1957	19	57	70.3	14	354	567	8.1	
G10S2060	20	60	74	16	393	628	9	
G10S2266	22	66	81.4	19	475	760	11.3	



Ručna oprema za podizanje tereta

Električna oprema za podizanje tereta

Poliesterske priveznice

Transportne trake za osiguranje tereta

Lanac, lančane priveznice i komponente

Čelična užad, priveznice i komponente

Oprema za šumarstvo

Oprema za premještanje tereta