


# POLIESTER PRIVEZNICE

## Karakteristike:


- Sklopovi sa 1, 2, 3 i 4 kraka pogodni su za sve vrste podizanja.
- Lakša alternativa u poređenju sa skupom lanaca ili skupom sajli.
- 100% poliester beskonačna priveznica u skladu sa EN 1492-2.
- Visokootporna oprema u skladu sa EN 1677.
- Koeficijent sigurnosti: 4:1

NAPOMENA: opciono  NFC identifikacija




Lifting Angle  $\beta$


## JEDNOKRAKA POLIESTER PRIVEZNICA

| Šifra   |  | Nosivost (t) | Product Code |
|---------|---|--------------|--------------|
| RSA-1-1 |   | 1            |              |
| RSA-1-2 |   | 2            |              |
| RSA-1-3 |   | 3            |              |
| RSA-1-5 |   | 5            |              |


## DVOKRAKA POLIESTER PRIVEZNICA

| Šifra   |  | Nosivost (t) | Nosivost (t) | Product Code |
|---------|---|--------------|--------------|--------------|
|         |   | Ugao $\beta$ | Ugao $\beta$ |              |
|         |   | 0-45°        | 45-60°       |              |
| RSA-2-1 |   | 1.4          | 1            |              |
| RSA-2-2 |   | 2.8          | 2            |              |
| RSA-2-3 |   | 4.2          | 3            |              |
| RSA-2-5 |   | 7            | 5            |              |

## TROKRAKA POLIESTER PRIVEZNICA

| Šifra   |  | Nosivost (t) | Nosivost (t) | Product Code |
|---------|---|--------------|--------------|--------------|
|         |   | Ugao $\beta$ | Ugao $\beta$ |              |
|         |   | 0-45°        | 45-60°       |              |
| RSA-3-1 |   | 2.1          | 1.5          |              |
| RSA-3-2 |   | 4.2          | 3            |              |
| RSA-3-3 |   | 6.3          | 4.5          |              |
| RSA-3-5 |   | 10.5         | 7.5          |              |

## ČETVOROKRAKA POLIESTER PRIVEZNICA

| Šifra   |  | Nosivost (t) | Nosivost (t) | Product Code |
|---------|---|--------------|--------------|--------------|
|         |   | Ugao $\beta$ | Ugao $\beta$ |              |
|         |   | 0-45°        | 45-60°       |              |
| RSA-4-1 |   | 2.1          | 1.5          |              |
| RSA-4-2 |   | 4.2          | 3            |              |
| RSA-4-3 |   | 6.3          | 4.5          |              |
| RSA-4-5 |   | 10.5         | 7.5          |              |

Ručna oprema za podizanje tereta

Električna oprema za podizanje tereta

Poliesterne priveznice

Transportne trake za osiguranje tereta

Lanac, lančane priveznice i komponente

Čelična užad, priveznice i komponente

Oprema za šumarstvo

Oprema za premještanje tereta